MAXHUB 01

V6 Classic Series

The Classic series is MAXHUB's most popular Interactive Flat Panel for meetings, collaboration and presentations for our corporate partners. Fulfilling the need for a device which can host remote meetings and local discussions for all sizes of organization from start-up teams to multinational companies.

MAXHUB V6 Classic Series of IFP brings together all the functions a meeting room needs, such as wirelessscreen sharing, whiteboarding, presenting as well as video conferencing with a high-quality camera and a wide microphone range. Every meeting room should have a MAXHUB V6 Classic series to enhance teamwork and increase organizational efficiency.





Professional 4K Display

High Color Accuracy, ΔE≤2 Wide Color Gamut, NTSC 90%



Touch Screen

20 Touch Points, Minimum Object Recognition - 2mm



Wireless Screen Sharing

Share your screen through MAXHUB Share app or wireless dongle




Smart Whiteboard

OCR supported,
Multiple built -in templates



Built-in Camera

48million pixels
Offer the best view in both dark/bright
scene with WDR technology




10th Gen Intel CPU

Powerful performance, fluid experience * With use of MAXHUB PC Module



Built-in Microphone

8 meters of voice pick-up 8 mics arrays, clear conversations



Built-in Speaker

2.1 Channel 2x 10W + 20W Classic Series

Display				
Model / Part No.	C5530	C6530	C7530	C8630
Diagonal Size (inch)	55	65	75	86
Backlight	Direct-lit LED	Direct-lit LED	Direct-lit LED	Direct-lit LED
Panel Technology	IPS	IPS	VA	VA
Aspect Ratio	16:9	16:9	16:9	16:9
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Refresh Rate	60Hz	60Hz	60Hz	60Hz
Response Time	8ms	8ms	8.5ms	8ms
Brightness (typ)	350cd/m ²	350cd/m ²	350cd/m ²	350cd/m ²
Contrast Ratio	1200:1	1200:1	5000:1	4000:1
Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°
Color Gamut (typ)	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Display Orientation	Landscape	Landscape	Landscape	Landscape
Operating Hour	16/7	16/7	16/7	16/7

Dimension&Weight				
Product Dimensions (WxHxD)	1263 x 776 x 88 mm 49.72 x 30.55 x 3.46 inch	1488 x 903 x 88 mm 58.58 x 35.55 x 3.46 inch	1709 x 1026 x 87 mm 73.35 x 44.88 x 8.86 inch	1957.1 x 1160.1 x 100.2 mm 77.05 x 45.67 x 3.94 inch
Shipping Dimensions (WxHxD)	1392 x 847 x 220mm 54.8 x 33.35 x 8.66 inch	1638 x 1005 x 208mm 64.09 x 39.57 x 8.19 inch	1863 x 1140 x 225 mm 73.35 x 44.88 x 8.86 inch	2110 x 1283 x 225 mm 83.07 x 50.51 x 6.86 inch
Net Weight (kg /pounds)	26.25kg / 57.87 lbs	36.25kg / 79.92 lbs	48.3kg / 106.48 lbs	59.75kg / 131.73 lbs
Gross Weight (kg /pounds)	34.2kg / 75.40 lbs	46.75kg / 103.07 lbs	62.8kg / 138.45 lbs	77.00kg / 169.76 lbs
Wall Mount (VESA)	400 x 200mm / 15.75 x 7.78inch	600 x 400mm / 23.62 x 15.75inch	800 x 400mm / 31.50x15.75inch	800 x 600mm / 31.50 x 23.62inch
Screws For VESA	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch

POWER				
Power Supply	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz
Max Power Consumption	300W	350W	400W	400W
Standby	≤0.5W	≤0.5W	≤0.5W	≤0.5W

Touch System	
Touch Sensor	IR Touch
Max Touch Points Supported	20
Accuracy	$\pm 1 \mathrm{mm}$
Object Recognition Range	≥2mm
Glass	Zero parallax , 3mm Angi-glare, Antibacterial
Supported Operating System (Touch Return)	Windows10/Windows8/Windows7/WindowsXP/ Android/Linux/Mac OS X/Chrome OS

Connectivity	
Input	HDMI IN x 1 , USB 2.0 x 1, USB 3.0 x 2, TOUCH 2.0 x 1 , USB Type-C x 2
Audio	Audio out x 1
Control	RS232 x 1
OPS Slot	Yes, 3840 x 2160@60fps
PC Module	MAXHUB PC Module
Wifi Module	SI06

Camera/Audio/Microphone		
Built-in Camera	Yes, Single Camera, 48MP	
Camera Features	Auto Frame / Speaker Tracking	
Built-in Speakers	2.1 Channel , 2x10W+20W	
Microphone Array	8 x Far-field, beam-forming microphone - max 8m range	

Environment	
Operating Temperature	0 °C ~40 °C
Storage Temperature	10%~90%RH
Operating Humidity	-20 °C ~60 °C
Storage Humidity	10%~90%RH

What's In The Box

Power Cord, 1 x Wifi Adapter, 2 x Passive Stylus, 1 x Wall Mount, 1 x Type-C Cable (1.8m | 70.9inch) Standard

Optional



















